



Representative Image

Catalog No. 274J3

Description: 25KV 200A LB JUNCTION 3PT SST BRCKT

UPC No 783786120369

Home > Medium Voltage Utility Solutions > Elastimold > Cable accessories

25kV 200 Amp, Loadbreak 3-Point Junction with Stainless Steel Bracket

Descriptors

Category	Cable accessories
Special Features	25kV, 200 Amp Loadbreak 3-Way Junction. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provides mating for other Elastimold loadbreak type products. Provides mating for Elastimold Elbow connectors. Mounting hardware for flat or curved mounting positions.
Application	Designed for subsurface, vault or padmount applications and can be used for sectionalizing, looping, tapping, and equipment bypass. Suitable for use on 25-kV class distribution systems, and rated for 200-ampere loadmake/loadbreak operation.

Specifications

Material	EPDM Rubber with Stainless Steel Bracket
Temperature Rating	-40 to +65 C

Classifications

Brand Name	Elastimold
Standard	ANSI/IEEE 386

Dimensions

Size	23.00 inch (584.2 mm) Mounting Frame Length, 4.00 inch (101.6 mm) Center to Center, 5.00 inch (127.0 mm) width. 9.60 inch (243.8 mm) height
------	---

Compliance and Certifications

RoHS	Out of scope of RoHS
------	----------------------