

Product details page



NYLBLOC™ LEGRAND

Bornera de regleta negro Nylbloc 16mm2 - 250V
REF. 034217 | CÓDIGO DE BARRAS. 3245060342173

> [Visite nuestro E-catálogo](#)

Características del producto:

- Nylbloc™ - connection strips and connectors without screwsNylbloc connection strips- 12 elements with captive screws- Supplied with screws undone- Flame retardant polypropylene (– 25 °C to + 100 °C)- Ambient temperature from – 25 °C to + 55 °C (T 55)- Conform to EN 60998-2-1 and EN 60664-1- Self-extinguishing to EN 60695-2-11 at 850°- Insulation voltage: 250 V according to EN 60 998-2-1- Use at 400 V integrated in a series of products that comply with the requirements of EN 60664-1, pollution degree 2, overload category III - Black - Rated capacity : 16 mm²mm²- Hole Ø : 5.5 mm- Max current : 76 A

Ejecución a prueba de explosión "Ex e"	Si
Tipo de conexión de eléctrica 1	Conexión roscada
Tipo de conexión de eléctrica 2	Conexión roscada
Tipo de montaje	Otros
Material del cuerpo aislante	Termoplástico

Clase de inflamabilidad de material aislante según UL94	Otros
Placa de cierre necesaria	No
Color	Negro
Transparente	No

Documentación:

Acuerdos y certificados

AENOR-030/000810 | (0.62Mo)