

Datasheet



PLEEXO LEGRAND

REF. LG-092062 | EAN. 3245060920623

[> Visit e-catalogue](#)

Technical characteristics

Max. conductor cross section	32 mm ²
Equipped with	None
Shape	Rectangular
Mounting method	Universal
Mounting in the soil	No
Mounting under water	No
For tube diameter	32 mm
Inlet from the rear	No
Length	240 mm
Width	190 mm
Depth	94 mm
Connectable	No
Number of inlets	14
Type of housing feed-through	Trimmable step membrane
Material	Plastic
Halogen free	Yes
Surface protection	Untreated
Colour	Grey
Degree of protection (IP)	IP55
Cover model	Other

Transparent cover	No
Cover attachment	Bayonet latch
Castable	No
Casting compound included	No
Sealable	Yes
Circuit integrity	None
With screening	No
Weatherproof	Yes
Operating / setting temperature	-25-40 °C
Explosion-tested version	No
For Ex-zone gas	None
For Ex-zone dust	None
degree of impact strength (IK)	IK07
Storage temperature	-25-70 °C
RAL-number	7035
Antimicrobial treatment	No
Label space/information surface	No
Entry membrane gland type	Flexible to cut
Vertical fixing center distance	80-80 mm
Horizontal fixing center distance	141-147 mm

Documentation

CAD & Design specs / BIM



3D_LG-092062.stp | IFC (3.86Mo)