BURNDY®

GB26, Mechanical Grounding Connector, Cable to Bar

By Burndy
Catalog # GB26

Mechanical Grounding Connector, Cable to 1/4″ Thick Bar, 4 AWG (Sol)-2/0 AWG (Str), 3/8″ Stud, Silicon Bronze Hardware.

Features

- High copper alloy ground connector for joining a range of cable to 1/4″ thick bar
- Type GB separates cable from bar
- One-wrench installation
- UL467 Listed
- Suitable for Direct Burial in earth or concrete

Application

For Copper Cable To Bar, Direct Burial Cable

General

Catalog Number	GB26
EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	240 lb-in
Material	Copper Alloy
Material Type - Screw	DURIUM™ Silicon Bronze
Physical Attribute - Screw Type	Hexagonal Bolt
Sub Brand	MECHANICAL CONNECTOR
Type	GB
UPC	781810231210
UPC 14 Digit GTIN	00781810231210

Dimensions

Dimension - Height inch	1.74 in
Dimension - Height mm	44.2 mm
Dimension - Width fraction	1-3/7 in
Dimension - Width inch	1.42 in

Conductor Related

Conductor - Copper Solid Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - Copper Solid Size Range	4 AWG-2/0 AWG
Conductor - Copper Str Size Range	4 AWG - 2/0 AWG

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Certification - UL Listed Direct Burial	Yes
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Carton Quantity	25
Minimum Pack Quantity	1

Product Assets

3D Models - GB26_MODEL-PDF
3D Models - GB26_MODEL-IGES
3D Models - GB26_MODEL-STEP
Catalogs - Burndy Grounding Catalog
Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_GB_Lineart
Sales Drawings - sc091657-01
Sell Sheets - Types GB, GBM for Copper Cable to Bar
Specifications - GB26