

YCS25RL, Aluminum Sleeve, Staked Cable Stop

By Burndy Catalog # YCS25RL

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 6-1/4 IN L.



- HYSPLICE Sleeve designed to withstand jumper loop tensile and vibration stresses
- Made of aluminum with staked-in cable stop
- Pre-Filled with PENETROX Joint Compound and Capped

Application

For ACSR, All Aluminum 6201, 5005 Compressed And Compact Conductors

00781810014998

General

Catalog Number	YCS25RL
Connector Type	Splice
Die Index	C or 247
EU RoHS Indicator	Yes
Material	Aluminum
Plated	Ν
Plating Type	Unplated
Prefilled Oxide Inhibitor	Υ
Sub Brand	UNISPLICE
Trade Name	UNISPLICE™
Type	YCS-RL
UPC	781810014998

Dimensions

inch

UPC 14 Digit GTIN

Dimension - B Length inch	3.03 in
Dimension - L Length Overall	158 mm
mm	
Dimension - Length Overall	6.22 in
inch	
Dimension - Outside Diameter	0.8 in

Conductor Related

Conductor - AAAC 5005 Size 1/0 (7) AWG



Conductor - AAAC 5005 Size	1/0 (7) AWG
Range	
Conductor - AAAC 6201 Size	1/0 (7) AWG
Conductor - AAAC 6201 Size	1/0 (7) AWG
Range	
Conductor - ACSR Str Size	1/0 (6/1) Raven AWG
Conductor - ACSR Str Size	1/0 (6/1) Raven AWG
Range	
Conductor - AL Str Size	1/0 (7) AWG
Conductor - AL Str Size Range	1/0 (7) AWG

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No
Logistics	

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	9800

Product Assets

3D Models - YCS25RL_MODEL-PDF
3D Models - YCS25RL_MODEL-IGES
3D Models - YCS25RL_MODEL-STEP
Catalogs - BURNDY Master Catalog - Section H - Overhead
Distribution
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_YCS25RL_LineArt
Sales Drawings - SD052277-01
Specifications - YCS25RL

