

YCS321RL, Aluminum Sleeve, Staked Cable Stop

By Burndy
Catalog # [YCS321RL](#)

HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), Index:655.

Features

- HYSPLICE Sleeve designed to withstand jumper loop tensile and vibration stresses
- Made of aluminum with staked-in cable stop
- Pre-Filled with PENETROX Joint Compound and Capped

Application

For ACSR, All Aluminum 6201, 5005 Compressed And Compact Conductors

General

Catalog Number	YCS321RL
Connector Type	Splice
Die Index	655
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	UNISPLICE
Trade Name	UNISPLICE™
Type	YCS-RL
UPC	781810015124
UPC 14 Digit GTIN	00781810015124

Dimensions

Dimension - B Length inch	2.25 in
Dimension - L Length Overall mm	131 mm
Dimension - Length Overall inch	5.16 in



Dimension - Outside Diameter 1.13 in
inch

Conductor Related

Conductor - ACSR Str Size	336.4 (18/1) Merlin
Conductor - AL Str Size	336.4

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	6000

Product Assets

[Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_YCS25RL_LineArt](#)
[Sales Drawings - SD..052277-01](#)
[Specifications - YCS321RL](#)