



YHD350, Line Tap Connector, AL-CU, AL-AL

By Burndy
Catalog # [YHD350](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors,wire diameter range,groove A(Run):0.461-0.563.

Features

- Wide range, Universal and Reversible Figure H Shapped aluminum compression connector
- Bendable tabs secure both run and tap conductors freeing the installers hands to work with the installation tool
- Massive aluminum design minimizes corrosion due to galvanic corrosion
- Pre-filled with PENETROX Joint Compound and individually packaged
- Conductor ranges and tooling is clearly printed on connector and package

Application

For Copper, Aluminum Or ACSR And Compact Conductors

General

Catalog Number	YHD350
Die Index	D3
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Trade Name	HYCRIMP™
Type	YHD
UPC	781810139301
UPC 14 Digit GTIN	00781810139301

Dimensions

Dimension - Height fraction	1-21/50 in
Dimension - Height inch	1.42 in
Dimension - Height mm	36.1 mm
Dimension - L Length Overall mm	57 mm
Dimension - Length Overall inch	2.25 in
Dimension - Width fraction	89/100 in
Dimension - Width inch	0.89 in
Dimension - Width mm	23 mm

Conductor Related

Conductor - ACSR Cmpt Run	1/0 AWG;2/0 AWG
Conductor - ACSR Cmpt Run Range	1/0 AWG-2/0 AWG
Conductor - ACSR Cmpt Tap	1 AWG;1/0 AWG;3/0 AWG;2/0 AWG
Conductor - ACSR Cmpt Tap Range	1 AWG-2/0 AWG
Conductor - ACSR Str Run	3/0 (6/1) Pigeon AWG;4/0 (6/1) Penguin AWG
Conductor - ACSR Str Run Range	3/0 (6/1) Pigeon AWG-4/0 (6/1) Penguin AWG
Conductor - ACSR Str Tap	1 (6/1) Robin AWG;1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Tap Range	1 (6/1) Robin AWG-2/0 (6/1) Quail AWG
Conductor - AL Str Run	3/0-4/0
Conductor - AL Str Run Range	3/0-4/0
Conductor - AL Str Tap	2/0 AWG;3/0 AWG
Conductor - AL Str Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Solid Run	250 - 300
Conductor - Copper Solid Run Range	250 - 300
Conductor - Copper Solid Tap	2/0 AWG;3/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG-3/0 AWG
Conductor - Copper Str Run	3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	3/0 AWG-4/0 AWG
Conductor - Copper Str Tap	1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	1 AWG-2/0 AWG

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity 200
Minimum Pack Quantity 25

Product Assets

3D Models - YHD350_MODEL-STEP
3D Models - YHD350_MODEL-PDF
3D Models - YHD350_MODEL-IGES

Catalogs - BURNDY Master Catalog - Section H - Overhead
Distribution
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_YH_LINEART
Sales Drawings - SD..073376-01
Specifications - YHD350



A Hubbell brand