SQUARE 11



Contactor, Type S, multipole lighting, electrically held, 60A, 3 pole, 220/240 VAC 50/60 Hz coil, open style [TAA]

8903SPO2V03

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor	
Туре	S	

Complementary

Control Circuit Voltage	240 V AC 60 Hz
	220 V AC 50 Hz
	220 V AC 30 TIZ
Current Rating	60 A
	3071
Number of Poles	3P
Control Units	No control units
	110 0011101 011110
Pilot Light	Without pilot light
Auxiliary Contacts	Without
	William
Other Options	None
Electrical Connection	Lugs
Height	5.5 in (140 mm)
Depth	4.9 in (125 mm)
Width	4.3 in (110 mm)

Environment

Enclosure Type	Not rated (open device) surface none	
Product Certifications	UL Listed CSA	

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901862246
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	7.00 in (17.78 cm)
Package 1 Width	6.50 in (16.51 cm)
Package 1 Length	9.50 in (24.13 cm)
Package 1 Weight	4.268 lb(US) (1.936 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances		
Packaging made with recycled cardboard	Yes	
Packaging without single use plastic	No	
China RoHS Regulation	China RoHS declaration	

Use Again

○ Repack and remanufacture		
Take-back	No	